

High Tension Spark Plug Lead

HT-HTL-XXxx

Features and Benefits

- Robust design
- High insulation value
- Various length
- High quality level
- Long life



High performance high tension spark plug leads for SPI Engines

The high performance PTFE spark plug leads from Huegli Tech are available in various lengths and dimensions. PTFE possesses a high inertness towards nearly all known chemicals. PTFE is insoluble in all solvents up to a temperature as high as 300°C (572°F)

Available Models

- HT-HTL TG 210 G5V TW86-B.....Tedom TG210
- HT-HTL-2330-Perkins.....Perkins 2330
- HT-HTL-DAEDONG.....Daedong XXX Serie
- HT-HTL-NTA855.....Cummins NTA855
- HT-HTL-TCG 2015.....Deutz TCG 2015
- HT-HTL-YC4GN.....Yuchai YC4GN
- HT-HTL0834/36.....MAN 0834/36
- HT-HTL26XX.....MAN 26XX Serie
- HT-HTL284X.....MAN 284X Serie
- HT-HTL28XX.....MAN 28XX Serie
- HT-HTL32XX.....MAN 3262-LE202
- HT-HTL32XX-Alt.....MAN 3262-LE202 / Altronic Coil
- HT-HTL32XX-18GZ5-77-2.....MAN 32XX Series with BERU M18 Spark Plug
- HT-HTL32XX-MR3D11360 M18.....MAN 32XX Series with Bosch M18 Spark Plug
- HT-HTL32XX-GL3-5.....MAN 32XX Series with Denso GL3-5 Spark Plug
- HT-HTL634S.....SISU 634S
- HT-HTL924/926.....Liebher 924 Serie
- HT-HTLDoosan GV158TI.....Doosan 158 Serie


Technical data

Electrical data

Dielectric Strength.....70kV/mm

Volume Resistivity..... 10^{18} Ohm cm

Local Distributor / Partner:



HUEGLI TECH AG (LTD)
Murgenthalstrasse 30
4900 Langenthal Switzerland
Phone: +41 62 916 50 30
Fax: +41 62 916 50 35

e-mail: sales@huegli-tech.com
www.huegli-tech.com