



# **Datasheet**

### **Product description**

Communication gateway with configurable interfaces between Modbus TCP/RTU, ComAp CAN, WebSupervisor and InteliScada protocols allowing user-defined interconnection of all attached devices

### **Key features**

- Bidirectional connectivity of 3rd party Modbus devices or ComAp controllers on CAN1
- Data buffering capability for avoiding loss of data during connectivity outage
- Inbuilt support of energy industry Modbus controlled devices (Inverters, BESS) from leading manufacturers
- Support for customizable user templates for any additional Modbus devices that are not inbuilt
- Dual ethernet interfaces decoupling trusted (private) and untrusted (public) network segments for enhanced cybersecurity





Order code: CM2GW300BAB

Communication module

InteliGateway 300 Datasheet Related HW ver: 1.0 Related SW ver: 2.2.0 Date of issue: 7/24/2023

## Dimensions, terminals and mounting





Unit: mm (inch)

**Weight**: 190 g

**Note:** The unit is mounted on DIN rail (35 mm/1.38 in)

InteliGateway 300 Datasheet

### **Technical data**

### **Power supply**

Power supply	8 to 36 V DC
Power consumption	up to 5 W

### **Operating conditions**

Operating temperature	- 20°C to + 70°C
Storage temperature	- 40°C to + 80°C
Operation humidity (norm 60068-2-30)	5 to 95% w/o condensation
Vibration	5 - 25 Hz, ± 1.6 mm 25 - 100 Hz, a = 4 g
Shocks	$a = 200 \text{ m/s}^2$

#### **Interfaces**

3x CAN port:	Galvanically separated, built-in terminating resistors are activated by jumper, Nominal impedance 120 $\Omega$
2x RS485 port:	Galvanically separated, built-in balancing and terminating resistors are activated by jumper
2x Ethernet port	RJ45, 100Mbit/s
1x USB device	Non-isolated type B connector (Not supported yet)

#### **Protocols**

Modbus TCP master	Up to 127 slave nodes supported
Modbus RTU master	Up to 16 slave nodes per each RS485 interface supported
ComAp I/O CAN	1 controller per CAN interface (CAN1 interface on Controller side)
ComAp Airgate	v1.0

#### **Other**

Data buffering	512MB

InteliGateway 300 Datasheet 3

#### **Certificates and standards**

- > EN61000-6-2
- > EN61000-6-4
- **>** UL6200
- > RINA





